

# Precont® PU4SK

Universal pressure transmitter / pressure switch  
for general industrial applications

Technical information TI06.25




## Application

- Machinery and plant engineering
- Air-conditioning and refrigeration plant engineering
- Hydraulic and pneumatic systems
- Process industry
- Environmental technology
- Facility and building automation

## Main features

- Measuring ranges from 250 mbar up to 600 bar
- Wide variety of process connections
- Robust ceramic front-flush or internal diaphragm
- Process temperature range -40°C to +135°C
- Fully welded robust steel enclosure
- High protection class IP69K/IP67
- Highest accuracy to  $\leq 0,15\%$
- Electronic 4...20mA FSK / RS485 Modbus®-RTU / IO-Link® / 0...10V
- Certification ATEX / IECEx: Ex ia IIC Ga / Ex ia IIIC Da
- Electrical connection M12 plug or angled plug



## Description

The device is an electronic pressure sensor for monitoring, control and continuous measurement of pressures in gases, vapors, liquids and dusts.

A high variety of versions of process connections and electronic types allows the use for a wide range of applications, also for demanding measuring requirements.

Due to its high accuracy and the digital adjustability by FSK, RS485 Modbus®-RTU or IO-Link® the device can be suited to a wide variety of applications.

The front-flush process connection enables the cleanability of the wetted diaphragm to be integrated into the process, also by CIP/SIP cleaning processes. Low-maintenance and trouble-free pressure measurement is thus also guaranteed in critical applications with viscose or also frequently changing media.

The long term stable and robust strain gauge ceramic measuring cell ensures reliable precise measuring values and allows the operation also at demanding environmental conditions, e.g. low temperatures, high shock and vibration loads or at problematic media. Customer specific special versions can be realized short-term on request, e.g. special designs for the process connection or other process materials.




FEEL FREE TO  
CONTACT US

Lauterbachstr. 57 1/2, D - 84307 Eggenfelden  
info@acs-controlsystem.com  
www.acs-controlsystem.com  
+49 8721-96680

# Technical Data

<b>Measuring range</b>										
Nom. pressure PN rel.	[bar]	-0,1...0	-0,1...0,1	-1...0	-1...1	0...0,05	0...0,1	0...0,2	0...0,4	0...0,6
<b>Output type A – Current 4...20mA FSK</b>										
Analogue output 4...20mA	3,9...20,5mA, Measuring range [08] = 4...20mA, error $\leq 3,9\text{mA} / \geq 20,5\text{mA}$									
Time behavior	$\leq 5\text{ms}$ (td = 0s)									
Interface	FSK / 1200 Bit/s									
<b>Output type V – RS485 Modbus®-RTU</b>										
Interface	RS485, bidirektional / Modbus-RTU / 4,8...38,4 kBaud									
Input resistance	112k $\Omega$									
Time behavior	$\leq 2\text{ms}$ (td = 0s)									
<b>Output type L – IO-Link®</b>										
Interface	IO-Link V1.1 / Port Class A / Com2 (38,4 kBaud), Com3 (230,4 kBaud)									
Analogue output	3,8...20,5mA, measuring range [08] = 4...20mA, error $\leq 3,6\text{mA} / \geq 21\text{mA}$ 0...20,5mA, measuring range [08] = 0...20mA, error $\leq 0,05\text{mA} / \geq 21\text{mA}$									
Time behavior	$\leq 2\text{ms}$ (td = 0s)									
Switch output	2x PP (Push-Pull), switch to +L/-L									
<b>Output type B - 0...10V</b>										
Signal range	0...10,25V, Measuring range [08] = 0...10V, error 0V / $\geq 10,25\text{V}$									
Time behaviour t90-min	$\leq 5\text{ms}$ (td = 0s)									
<b>Auxiliary power</b>										
Supply voltage Us / Input current Is / Ready delay time	Type A – 4...20mA FSK: 9...35VDC reverse polarity protected / Ripple voltage $\leq 2\text{Vpp} / \leq 20,5\text{mA} / \leq 0,1\text{s}$ (td = 0s) Type A – 4...20mA FSK Ex: 9...30VDC / $\leq 2\text{Vpp} / \leq 22\text{mA}$ Type B – 0...10V: 14...35VDC reverse polarity protected / Ripple voltage $\leq 2\text{Vpp} / \leq 25\text{mA}$ (Iuo = 0mA) / $\leq 0,1\text{s}$ (td = 0s) Type V – RS485 Modbus®-RTU: 6...35VDC reverse polarity protected / Ripple voltage $\leq 2\text{Vpp} / \leq 10\text{mA}$ (Co = 0mA) / $\leq 0,1\text{s}$ (td = 0s) Type L – IO-Link® inactive: 9...35VDC reverse polarity protected / Ripple voltage $\leq 2\text{Vpp} / \leq 20\text{mA}$ (Co / So / Io = 0mA) / $\leq 0,1\text{s}$ (td = 0s) Type L – IO-Link® active: 18...30VDC reverse polarity protected / Ripple voltage $\leq 2\text{Vpp} / \leq 20\text{mA}$ (Co / So / Io = 0mA) / $\leq 0,1\text{s}$ (td = 0s)									
<b>Measuring accuracy</b>										
Characteristic deviation	$\leq \pm 0,05\%\text{FSI} / \pm 0,1\%\text{FSI} / \pm 0,2\%\text{FSI}$									
Long term drift zero	$\leq \pm 0,15\%\text{FSI}/\text{year}$									
Influence temperature	Tk $\leq \pm 0,05\%\text{FSI}/\text{K}$									
<b>Process conditions</b>										
Process temperature	Standard: -40...+100°C (-40°F...+212°F) Extended: -40...+135°C (-40°F...+275°F) / +140°C (+284°F) – 1h FKM/FPM: -25...+140°C (-13°F...+284°F) EPDM: -40...+140°C (-40°F...+284°F) ATEX/IECEX: acc. to certificate ATEX/IECEX									
Pressure cycles	$\geq 100$ Mio. (1,2xPN)									
<b>Environmental conditions</b>										
Environmental temperature	-40°C...+100°C / ATEX/IECEX: see certificate									
Protection level	IP69K/IP67 (EN/IEC 60529)									
MTTF	4...20mA: 745 years / 0-10V: 610 years / RS485 Modbus®-RTU: 561 years / IO-Link®: 601 years									

## Electrical connection



# Dimensions (mm)

Plug M12 [14-S]	Plug EN 175-301-803-C [14-C]	Plug EN 175-301-803-A [14-A]
<p>Technical drawing of Plug M12 [14-S] showing dimensions: M12x1 top thread, 10mm top section, 26mm diameter, 27mm hex nut, 16,5x11,6x1,5 ISO 1179-2 E connector, 13mm connector length, 2mm gap, G 1/4" A bottom thread, and diameters of 3,5, 5, and 9,5mm.</p>	<p>Technical drawing of Plug EN 175-301-803-C [14-C] showing dimensions: 28mm top section, 50mm total length, 26mm diameter, 27mm hex nut, 16,5x11,6x1,5 ISO 1179-2 E connector, 13mm connector length, 2mm gap, G 1/4" A bottom thread, and diameters of 3,5, 5, and 9,5mm.</p>	<p>Technical drawing of Plug EN 175-301-803-A [14-A] showing dimensions: 36mm top section, 49mm total length, 26mm diameter, 27mm hex nut, 16,5x11,6x1,5 ISO 1179-2 E connector, 13mm connector length, 2mm gap, G 1/4" A bottom thread, and diameters of 3,5, 5, and 9,5mm.</p>

Thread ISO 228-1 - G1/4", EN 837 [04-6]	Thread ISO 228-1 - G1/2", EN 837 [04-1]
<p>Process pressure P<sub>max</sub> = 600 bar Torque M<sub>max</sub> = 50Nm</p>	<p>Process pressure P<sub>max</sub> = 600 bar Torque M<sub>max</sub> = 50Nm</p>
<p>Technical drawing of Plug with G1/4" thread showing dimensions: M12x1 top thread, 10mm top section, 26mm diameter, 27mm hex nut, 16,5x11,6x1,5 ISO 1179-2 E connector, 13mm connector length, 2mm gap, and diameters of 3,5, 5, and 9,5mm.</p>	<p>Technical drawing of Plug with G1/2" thread showing dimensions: M12x1 top thread, 10mm top section, 26mm diameter, 27mm hex nut, 23,9x18,5x1,5 ISO 1179-2 E connector, 17mm connector length, 20mm total length, 3mm gap, 17,5mm diameter, and diameters of 3 and 6mm.</p>

Further terminal assignment and dimensional drawings can be found in the operating instructions or in the technical information.

# Order code

Type  
PU4S Standard

K	<b>Measuring system – material diaphragm (process wetted) / sensor type</b> Ceramic Al2O3 96% / strain gauge
S	<b>Approval</b> Standard
X	ATEX II 1 G / IECEx Ex ia IIC Ga resp. ATEX II 1 D / IECEx Ex ia IIIC Da (only Output type – A and Electrical connection – S)
3	<b>Process connection</b> Thread ISO 228-1 – G¼"A, ISO 1179-2 E
6	Thread ISO 228-1 – G¼"A, EN 837 (Manometer)
4	Thread ISO 228-1 – G¼"I, internal thread
1	Thread ISO 228-1 – G½"A, EN 837 (Manometer)
2	Thread ISO 228-1 – G½"A, ISO 1179-2 E, internal drill
8	Thread ISO 228-1 – G¾"A, ISO 1179-2 E, front-flush
5	Thread ISO 228-1 – G1"A, ISO 1179-2 E, front-flush
E	Thread ANSI – NPT ¼"
C	Thread ANSI – NPT ½"
Y	others
1	<b>Material process gaskets (process wetted)</b> FPM – fluorelastomere (e.g. Viton®)
3	EPDM – ethylene-propylene-dienmonomere, FDA-listed
Y	others
V	<b>Material process connection (process wetted)</b> CrNi-steel
C	<b>Material terminal enclosure</b> CrNi-steel
02	<b>Measuring range</b> 0...250 mbar
03	0...400 mbar
04	0...600 mbar
05	0...1 bar
06	0...1,6 bar
07	0...2,5 bar
08	0...4 bar
09	0...6 bar
10	0...10 bar
11	0...16 bar
12	0...25 bar
13	0...40 bar
14	0...60 bar
19	0...100 bar
20	0...160 bar
21	0...250 bar
22	0...320 bar
23	0...400 bar
24	0...600 bar
16	-1...0 bar
17	-1...+1 bar
YY	Special measuring range
A	<b>Electronic – output</b> Current 4...20mA, FSK, 2-wire
B	Voltage 0-10V, 3-wire (only with Electrical connection – C or A)
V	RS485 Modbus®-RTU, 4-wire (only with Electrical connection – S)
L	IO-Link®, 1x current 0/4...20mA / 2x switch, 4-wire (only with Electrical connection – S)
S	<b>Electronic – function</b> Standard
0	<b>Process temperature</b> Standard –40°C...+100°C
1	Extended –40°C...+135°C, temperature decoupler
R	<b>Pressure type</b> Gauge pressure
A	Absolute pressure, ≥ 1bar ... ≤ 40bar
4	<b>Measuring system – accuracy</b> 0,5%
8	Xcellence – 0,15%, linearization protocol
S	<b>Electrical connection</b> Plug M12x1
C	Plug EN 175-301-803-C (DIN 43650-C)
A	Plug EN 175-301-803-A (DIN 43650-A)
-SF	<b>Additional options</b> LABS-free, silicone-free / paint compatible version
-ML	Measurement point designation / TAG – Laser marking
-MZ	Material test certificate – EN10204 3.1
-WT	Factory certification – drink water suitability
-KF	Configuration / Preset
-WK	Factory calibration – calibration certificate

Precont® PU4S

K V C S